## IN THE CLAIMS

The following is a complete listing of the claims, which replaces all previous versions and listings of the claims.

- 1. (currently amended) A cable management system, comprising:
- a flexible cable harness adapted to support at least one electrical cable, the flexible cable harness including a flexible spine and a plurality of straps secured to the flexible spine, wherein the harness is not adapted to conduct electricity to an electronic device;
  - a first support member securable to the cable harness; and
- a second support member securable to the cable harness, wherein the harness is suspended between the first and second support members.
- 2. (original) The cable management system, as set forth in claim 1, wherein the first support member comprises wire.
- 3. (original) The cable management system, as set forth in claim 2, comprising a first reel, the first support member being wound thereon.
- 4. (original) The cable management system, as set forth in claim 3, wherein the first reel is adapted to retract the first support member onto the first reel.
- 5. (original) The cable management system, as set forth in claim 3, wherein the at least one electrical cable is securable to a movable electronic device disposed within a chassis, the first reel being movable with the electronic device.
- 6. (previously presented) The cable management system, as set forth in claim 5, wherein the first support member is unwound from the first reel as the electronic

device is moved from a first position to a second position relative to the chassis and retracted as the electronic device is moved from the second position to the first position.

- 7. (original) The cable management system, as set forth in claim 6, comprising a second reel movable with the electronic device and having the second support member wound thereon, wherein the second support member is unwound from the second reel as the electronic device is moved from a first position to a second position relative to the chassis and retracted as the electronic device is moved from the second position to the first position.
- 8. (original) The cable management system, as set forth in claim 1, wherein the first support member is secured to the harness at a first location along the harness and the second support member is secured to the harness at a second location along the harness.
- 9. (original) The cable management system, as set forth in claim 1, wherein the harness is adapted to be secured to a movable electronic device disposed within a chassis.
- 10. (original) The cable management system, as set forth in claim 9, wherein the harness is adapted to be secured to the chassis.
- 11. (original) A cable management system, comprising:
  means for securing a harness to at least one electrical cable secured to a movable electrical device;

means for supporting the harness from a first flexible member; and means for supporting the harness from a second flexible member.

- 12. (original). The cable management system, as set forth in claim 11, wherein the movable electrical device is movable relative to a storage rack adapted to house the movable electrical device.
- 13. (original) The cable management system, as set forth in claim 12, wherein the cable management system coils the flexible member as the movable electrical device is moved toward a first position relative to the rack.
- 14. (original) The cable management system, as set forth in claim 12, wherein the cable management system uncoils the flexible member as the movable electrical device is moved toward a second position relative to the rack.
- 15. (original) The cable management system, as set forth in claim 11, wherein the electrical device has a top surface and a bottom surface and the cable management system is adapted to maintain the portion of the at least one electrical cable secured to the harness below the top surface of the electrical device and above the bottom surface of the electrical device.
- 16. (currently amended) A method of assembling a cable management system, comprising:

securing a harness to at least one electrical cable secured to a movable electrical device;

coupling a first flexible member to the harness to enable such that the first flexible member to supports the harness therefrom; and

coupling a second flexible member to the harness to enable such that the second flexible member to supports the harness therefrom.

- 17. (original) The method of assembling, as set forth in claim 16, wherein coupling a first flexible member to the harness comprises connecting a first wire from a reel to a first portion of the harness.
- 18. (original) The method of assembling, as set forth in claim 17, wherein coupling a second flexible support member to the harness comprises connecting a second wire from a reel to a second portion of the harness.
- 19. (original) The method of assembling, as set forth in claim 16, comprising securing the cable harness to the movable electronic device.
- 20. (original) The method of assembling, as set forth in claim 19, comprising securing the cable harness to a support housing for the electronic device.
- 21. (currently amended) A cable management system for a movable device, comprising:
- a flexible harness securable to at least one cable coupleable to the movable device; and
- a first support member coupled to the device and secured to the harness, wherein the at least one cable is suspended from the first support member such that the first support member to suspend and to support supports a first portion of the at least one cable as the device is moved.
- 22. (original) The cable management system, as set forth in claim 21, wherein the first support member comprises a first reel, the first reel having a first line wound thereon, wherein the first reel is spring-loaded to maintain a tensile force on the first line.

- 23. (original) The cable management system, as set forth in claim 21, comprising a second support member coupled to the device and securable to the harness to suspend a second portion of the at least one cable as the device is moved.
- 24. (original) The cable management system, as set forth in claim 23, wherein the second support member comprises a second reel, the second reel having a second line wound thereon, wherein the second reel is biased to maintain a tensile force on the second line.
- 25. (original) The cable management system, as set forth in claim 23, wherein the harness comprises a connector operable to suspend a third portion of the at least one electrical cable from the device.
- 26. (original) The cable management system, as set forth in claim 23, wherein the harness comprises a connector operable to suspend a fourth portion of the at least one electrical cable from a fixed member.
- 27. (original) The cable management system, as set forth in claim 21, wherein the flexible harness comprises a flexible spine and a plurality of straps secured to the spine and operable to capture the at least one cable.
- 28. (previously presented) The cable management system, as set forth in claim 27, wherein the plurality of straps comprise a self-securing material.
- 29. (currently amended) The cable management system, as set forth in claim 1, wherein the first support member comprises an expandable extendable support assembly.
- 30. (currently amended) The cable management system, as set forth in claim 29, wherein the expandable extendable support assembly comprises a reel and a wire.

- 31. (currently amended) The cable management system, as set forth in claim 1, wherein the second support member comprises an expandable extendable support assembly.
- 32. (currently amended) The cable management system, as set forth in claim 31, wherein the expandable extendable support assembly comprises a reel and a wire.
- 33. (previously presented) The cable management system, as set forth in claim 1, wherein the harness is suspended from the first and second support members.